

JIS G3444 一般構造用炭素鋼鋼管

材質:STK400とSTK490通用です

外径 (mm)	厚さ (mm)																												
	2.0	2.3	2.5	2.8	3.2	3.5	3.6	4.0	4.5	5.0	5.3	5.8	6.0	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7		
21.7	2.0																												
27.2	2.0	2.3																											
34.0	2.3																												
42.7	2.3	2.5																											
48.6	2.3	2.5	2.8	3.2																									
60.5	2.3	2.5	2.8	3.2	3.5	3.6	4.0																						
76.3	2.8	3.2	3.5	3.6	4.0																								
89.1	2.8	3.2	3.5	3.6	4.0																								
101.6	3.2	3.5	3.6	4.0	4.5	5.0																							
114.3	3.2	3.5	3.6	4.0	4.5	5.0																							
139.8	3.6	4.0	4.5	5.0	5.3	5.8	6.0																						
165.2	4.5	5.0	5.3	5.8	6.0	6.4	6.6	6.9	7.0	7.1																			
190.7	4.5	5.0	5.3	5.8	6.0	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2																
216.3	4.5	5.0	5.3	5.8	6.0	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2																
267.4	6.0	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2	9.0	9.3																		
318.5	6.0	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2	9.0	9.3	9.5	10.3																
355.6	6.4	6.6	6.9	7.0	7.1	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7															
406.4	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0																	
457.2	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0																	
500.0	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0																	
508.0	7.9	8.0	8.2	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0	22.0																
558.8	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0	22.0																			
600.0	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0	22.0																			
609.6	9.0	9.3	9.5	10.3	12.0	12.7	14.0	16.0	19.0	22.0																			

注・製造工場は天津双街鋼管有限公司

川崎市中原区木月2丁目2番34号
 株式会社鈴木エンタープライズ
 TEL 044-433-6399 FAX 044-434-8488